

PRODUCT No.: 1442
1444
1446

FONDO DE JUNTAS SUPPORT FOR JOINT SEALING

DESCRIPTION:

Circular section, rotproof cord, made of closed polypropylene cells with different sections. It's air and water tight and ideal as joint bottom to seal afterwards with **SATECMA® ELASTIC PM 33** or **P-400** or other mastics.

SURFACE CONDITIONING:

The space where the joint is to be placed must be clean and dry, with a uniform section in order to determine the most suitable cord.

METHOD OF USE:

The **FONDO DE JUNTAS** should be lightly wider than the joint, in order to allow it to be tight against the joint sides. It will be below the upper edge of the joint at a depth which allows placing the suitable thickness of sealing cord. As minimum thickness we recommend 1 cm. When pressing down, do not use cutting tools.

TECHNICAL CHARACTERISTICS:

Density	:	3,5 kg./m ³ .
Closed cellular structure		
Rotproof, chemically and physically neutral		
Thermal conductivity at 0 °C	:	0,035/Kcal/mh °C
Temperature resistance in continuous rating	:	-70° a 90° C
Ageing resistance (cycles) (-70° C --+ 85° C)	:	(10 cycles) No deficiencies.
Ozone resistance	:	Good
Water absorption (weight) after 24 hours	:	1%

PACKAGING:

- Available sections 10,20 and 50 mm. diameter

ED.1995/2