

PRODUCT N°.:4213

TECMACRIL FACHADAS

ACRYLIC PAINT FOR FAÇADES

DESCRIPTION:

TECMACRIL FACHADAS is a water-borne acrylic coating for decorating and protecting façades against aggressions from external agents such as rain, pollution, etc. The product offers waterproofing and good transpirability characteristics which allow the natural vapour exchange between both sides of the façade.

CHARACTERISTICS:

Nature	: Acrylic
Adherence	: Perfect on a great range of supports
Dilutant	: Water
Yield	: 4 m ² / kg, approx. several coats
Application	: Brush or roller
Drying time 20°C and 55%R.H	: Touch 1 hour – Repainted 6 hours
Colours	: White, Bay Cream, Sahara Yellow, Toledo Ocre, Pale Salmon

PROPERTIES:

Álcali, water and UV resistente. It does not get yellow.
Excellent repainting capability
Good transpiration
Very good adherence to a great range of supports.

FIELD OF APPLICATION:

Protection of façades made of concrete, mortar, masonry, brick, gypsum, etc.

SURFACE CONDITIONING:

Surfaces should be dry and free from grease, oil, loose particles, dust or any other pollutant. Grout has to be removed by mechanical blasting or by attacking with our **DESCA-2F**, rinsing afterwards with plenty of water. The surface should have some roughness and porosity in order to allow a good adherence to the coating. When applying over other paint, loose or cracked paint should be removed.

METHOD OF USE:

Stir the contents in the containers before applying. Apply a first coat diluted with 10-15 % water. After 4-6 hours, depending on the weather conditions, it'll be posible to apply a second coat, without dilution this time.

SPECIAL RECOMMENDATIONS:

- Do not apply with temperatures below 10 °C or when relative humidity is above 85%.
- Do not apply when rain is expected.

STORAGE AND PACKAGING:

TECMACRIL FACHADAS is packaged in 10 and 25 kg metal drums. The product should be stored in a cool place, protected from frost, not exposed to high temperatures.

ED.2002/1